

| Kinetics Camera (B002058) | | | Princeton Instruments | | |
|---------------------------|-----|--|-----------------------|-----------------|------------------|
| Item | Qty | Description | Unit Price | Discount | Total Price |
| 1) | 1 | ProEM: 512BK_Kinetics 8244-0001 -7555-0003, EMCCD Camera System Permanent Vacuum guarantee Thermoelectrically cooled camera head. • Proprietary frame transfer, back-illuminated EMCCD With custom on-chip mask • Three modes of operation: 1) Fast kinetics (2 rows open) 2) Variable Kinetics 3) Frame transfer • Includes External, adjustable shutter/slit assembly • Gigabit Ethernet (GigE) data interface • 16-bit dual EMCCD (10MHz and 5MHZ) and Normal CCD (5MHz, 1MHz, and 100kHz) readout ports • C-mount (Adjustable c-to-spectrometer Kinetics Adapter, 7050-0104 | \$52,500.00 | \$5,250.00 | \$47,250.00 |
| 2) | 1 | LightField/64 • Real-time acquisition, display, and data processing software for Microsoft Windows Vista/7 (64-bit) | \$3,950.00 | \$1,975.00 | \$1,975.00 |
| 3) | 1 | F-mount to C-mount Adap09005326-001 • F-mount to C-mount Adapter (nik-2360) | 250.00 | 25.00 | 225.00 |
| | | | 56,700.00 | 7,250.00 | 49,450.00 |
| | | FOB | UAHuntsville | | |
| | | TERMS | Net 30 | | |
| | | WARRANTY | 1 years | | |
| | | ESTIMATED DELIVERY | 8-12 weeks | | |
| | | YOUR REFERENCE NO. | 130028 | | |
| | | QUOTATION EFFECTIVE UNTIL | 4/30/2011 | | |
| | | BUSINESS CLASSIFICATION | | | |
| | | Bid awarded to Princeton Instruments, Inc. as the lowest responsible bidder meeting specs. | | | |